

THE KAIVAC® 1250

EQUIPMENT SPECIFICATIONS

DESCRIPTION

Water Tank	12 Gallons (45, 42 l)
Spray Time	16 Minutes
Flow Rate	.75 GPM (2,8 l/min)
Pressure (at gun)	500 psi (34,5 bars)
Vac Tank	8 Gallons (30,27 l)
See-Through Vac Tank	Yes
Dump Hose	26" (66 cm) Long
Toilet Dumping	100% @ 27 secs
Vac Tank Cleanout	Yes
Method of Dumping	Drain Hose
Vac Motor Lift	108" (274 cm)
Vac CFM	112 cfm (3172 l/min)
HEPA Blow Feature	300 mph (482,7 km/h)
DVD Player	Optional
HEPA Filtered Exhaust	Yes - Replaceable

CHEMICAL

Molded-In Chemical Holder	Gallon (1), Quart (2)
Chemical Switching	Single/Quick Change
Safety Cap System	Yes
Metering Tip Settings	5 Settings

ELECTRICAL

(Safety Certified by Entela to ANSI/UL #1017)

Volts (U.S.)	110 Volt - 60 Hz
Volts (Universal)	100-240V; 50-60Hz
Amps Total	14.5 amp
GFCI	Yes

CORDS AND HOSES

Vac Hose	35 ft. (10,67 m) Slinky
Spray Line	32 ft. (9,75 m)
Quick-Connect Gun	Yes
Electric Cord	25 ft. (7,6 m)
Blow Hose	33 ft. (10 m) Slinky

BODY

Rotational Mold	Yes
Removable Engine Compartment	Yes
Weight	93.5 lb. (42.41 kg)
Size (H x L x W)	38" x 22" x 20" (96,5 x 55,9 x 50,8 cm)
Hard Rubber Tire	(2) 5" (12,7 cm)
Casters	(2) 4" (10,2 cm), locking
Stair Climbing Wheels	Yes
Handle	Molded-In
Parking Brake	Yes

TOOLS INCLUDED

Vac Wand Aluminum	2-Piece
14 Inch Squeegee Head	Yes
Blow Nozzle	Yes
Training Materials	Video and Placard
KaiBrush	Yes
Window Squeegee	Yes
Metering Tip Kit	Yes
KaiDrain	Yes
15 Gallon Tote Bag	Yes

WARRANTY WITH KAIVAC CHEMICAL USAGE

Body	10 Years
Parts	3 Years
Labor	1 Year



kaivac cleaning systems™

Complete Cleaning For Healthy Results™